














Mod. 441

	Attacco quadro Square drive Carré d'entraînement Antriebsvierkant	1/2 "
	Capacità bullone Bolt capacity Capacité boulon Bolzengröße	12 mm
	Velocità a vuoto Free speed Rotation à vide Drehzahl	400 giri/min
	Coppia massima - avvitamento/svitamento Max torque – tighten/loosen Couple max. – vissage/dévisage Max Drehmoment	95 Nm
	Pressione aria raccomandata Air pressure Pression d'utilisation Luftdruck	6,2 bar
	Attacco aria Air connection Raccord Luftanschluß	1/4" BSPT
	Diametro interno tubo aria Air hose internal diameter Diamètre intérieur du tuyau de l'air Innendurchmesser Luftschlauch	8 mm
	Consumo aria medio Average air consumption Consommation d'air moyenne Luftverbrauch	5 l/sec
	Peso Weight Poids Gewicht	1,30 kg
	Lunghezza Length Longueur Größe	280 mm
	Pressione sonora Sound pressure Pression acoustique Schalldruckpegel	90 ± 3 dB(A)
	Potenza sonora Sound power Puissance acoustique Schalleistung	96 ± 3 dB(A)
	Vibrazioni Vibration level Niveau de vibration Beschleunigung	15,3 m/sec ²

